

FRESH AIR HIGH LIMIT ELECTRONIC THERMOSTAT



Made in Australia
 100% Australian Owned Company



Features

- Australian Made and designed
- Power Supply 24V AC or DC
- 10 Amp (Resistive) Potential free relay contacts
- L.E.D Indication of all output status


Use

The HLW1 Thermostat is primarily designed for use as a O/A wall mount high limit fresh air thermostat, typically used to break a 0-10v dc Y economy cycle signal controlling the position of damper motors. Or to override the position of 2 position damper motors.
 The output relay is voltage free permitting use on either 240, 24 AC circuits or DC control signal circuitry. Switch point is adjustable with it's status displayed via red / green LED indicators.
 The HLW1 thermostat is ideally suited for outside wall mounting perferably on a south facing wall or a location not exposed to the sun or other heat sources.

Technical Data

General Specifications	Operating Voltage	24 Volts AC or DC
	Power Consumption	24 Volts 1 VA
	Switching Capacity of Relays	
	Voltage	AC 0...250 Volts
	Current	10 (3) A
	Setpoint Setting Range	16...28 oC
	Switching Differential	1 oC (NON Adjustable)
	Output Indication	
	Tripped	Red LED
	OK for cooling	Green LED
Environmental Conditions	Operation	
	Ambient Temperature	0...45oC
	Humidity	< 95 % RH (Non Condensing)
	Storage and Transport	
	Ambient Temperature	-5...65oC
	Humidity	< 90 % RH (Non Condensing)
Product Standards	C-tick	N10842
Weight	Including Packaging	150 grams
Housing	Colour	Black
	Material	ABS POLYCARB
	UV Stabilised	YES
	Fire Retardant	YES
	Size	L130mm x W120mm x D35mm
	Mounting Method	Wall mount 4 screw locations

Terminal Designations



- 24 24 Volt Supply Active AC or DC
- N 24 Volt Supply Neutral
- COM Relay common
- C N/C CONTACT (ok for cooling) = green led on
- RVH N/O CONTACT (hi-limit action) = red led on

Application Example's

